

SLICAN CCT-1668

ARE YOU OWNER OF SMALL OR MEDIUM ENTERPRISE?

FOR SURE YOU NEED SMALL BUT TECHNICALLY SOPHISTICATED COMMUNICATION SOLUTION.

UNIVERSAL SYSTEM WHICH, WILL GROW UP TOGETHER WITH YOUR BUSINESS.

ONE PRODUCT, WHICH WILL JOIN TOGETHER POSSIBILITIES OF SEVERAL PRODUCTS – INCLUDING VoIP AND GSM GATEWAYS AS WELL AS CALL RECORDING.

SOLUTION, ECONOMICALLY ATTRACTIVE DURING PURCHASE, AND PRODUCT WHICH WILL DECREASE YOUR MONTHLY COMMUNICATION EXPENSES.

WE HAVE SOLUTION FOR YOU AND YOUR COMPANY!
CHOOSE SLICAN CCT-1668!



■ CCT-1668.L



■ CCT-1668.S



■ CCT-1668.EU

FLEXIBLE SYSTEM

EFFICIENT COMMUNICATION

SAVINGS

I CHOOSE:

INNOVATIVE USER SOLUTIONS:

ICD – Intelligent Call Distribution

All incoming calls will be automatically transferred to specified person or departments at your company – e.g. all calls from foreign countries will be forwarded to Export Department and calls from domestic market to person responsible for described region of country.

PATHFINDER – fast and efficient communication

Due to unique system of automatic call path routing in Slican server, your customer calling back on number shown on his mobile will be connected directly to that person who called him before.

INVENIO – efficient and modern communication for incoming calls

Offer to your customers something more than standard Infolinie. Slican Invenio is comfortable and user friendly system of information and navigation for all people calling your company.

VoIP telephony

Now, due to embedded VoIP module in Slican's servers, you may call via alternative VoIP providers and call for really low prices. Embedded VoIP Gateway in CCT-1668 will ensure you both, lower invoices and high quality of connections.

GSM telephony

Embedded GSM gateway is ideal solution for company using corporation network. From now here on high quality GSM in low price may be realised also from / to usual system phone extension.

EbdRec – embedded call recording

To record and archive all calls you do not have to buy external devices now!. Embedded recording in CCT-1668 server is efficient and user friendly



SLICAN CCT-1668

PARAMETERS				
PABX type		CCT-1668.S	CCT-1668.L	CCT-1668.EU
Standard configuration – analogue ports		8	16	16
Maximal capacity	Analogue trunks (ASS)	12	40	40
	Analogue ports (AB)	32	88	88
	ISDN BRA trunks (int./ext.)	12/11	12/11	12/11
	ISDN PRA trunks	-	1	1
	VoIP channels	8	8	8
	VoIP subscribers	118	118	118
	GSM trunks / cards	2	4	4
	CTS system ports Up ₀ / IP	18/18	18/18	18/18
	Call recording channels	12	12	12
Available Slican devices		Digital system phones Slican CTS-202, CTS-202.Plus and CTS-202.IP		
		Analogue phone XL-2023ID		
		Slican CTS-232 console		
		Slican BRF and BRV doorphones		
		Multi Audio Box (MAB-1101)		
Applications supporting CCT-1668		Slican TelefonCTI.plus / TelefonCTI		
		Slican BillingMAN.plus / BillingMAN		
		Slican PayMAN		
		Slican RecordMAN		
VoIP parameters		Supported protocols SIP and IAX2 (voice codecs G.711, G.729, GSM 6.10 FullRate)		
		Supporting third parties application/ devices „softphone” type application or hardware IP phone, IP gateway		
		Supported system phones Up to 18 Slican CTS-202.IP system phones and 100 from another supplier		
		Working mode VoIP master or slave		
Power supply		~230 V; 50 Hz; < 60 VA	~230 V; 50 Hz; < 120 VA	~230 V; 50 Hz; < 120 VA
Wymiary (mm) szerokość x wysokość x głębokość		250 x 272 x 120	412 x 488 x 120	483 (19”) x 178-(4U) x 225
PROTOCOLS				
Voice communication protocols		POTS/ ISDN-EDSS1/ SIP v.2.0/ IAX2/ GSM900/1800/ Up ₀		
Server communication protocols		CTIP/ USRP/ PayMANP/ HotelP/ TAPI CSTA via OSITRON/ Ethernet		
FUNCTIONALITY				
<ul style="list-style-type: none"> • embedded VoIP and GSM gateways • support for mobile users: Universal Message DND/ Follow Me • possibility of creating networks based on servers MAC-6400 and CCT-1668 • local connection to computer via LAN or USB • remote on-line monitoring of PBX via modem and Internet • internal memory of system and charging events • charging of PABX internal calls • service of external numbering as internal • cooperation with other PABXes, external software and external VoIP gateways • service of „cheap minutes” limit • service of users balance 				



CHOOSE BETTER COMMUNICATION !